



Key to symbols



Minimum Height



Maximum Height



Closed Length



Footprint Diameter



Weight



Spigot Size



Socket Size



Grip Head Size



Top Tube Diameter



Suggested Wheels



Maximum Evenly Distributed Load on Level Ground



Patented



German Safety Standard

The products with the TÜV-GS symbol are developed and tested in accordance with DIN 15560 norm.

B **CB** **J**

Ordering

Products may be ordered by using the product code together with its title. Optional Black (B) finish, Black Chrome (CB) finish, and 17mm female attachment (J) versions are available where indicated. Add B, CB, or J to the product code when ordering.

i.e.

A2025F **CB** **J**

Lighting Stand don't fall inside the European directive 98/37/CE and for this reason they don't need "CE" mark



All Avenger products are designed, engineered and made in Italy

WIND UP STANDS



B6026CS (REPLACES B205)

IR WIND UP STAND 26 WITH BRAKED WHEELS









60.2in	102.8in	68.1in	59.8in	41.8lbs
99lbs	28mm 1" 1/8"	16mm 5/8"		

Chrome steel stand.
2 sections, 1 riser. Ø: 55, 45mm.
Leg Ø: 30mm.
1 leveling leg.



B6030CS (REPLACES B201)









**WIND UP STAND 30 LOW
BASE WITH BRAKED WHEELS**

				
60.2in	116.5in	68.9in	55.9in	39.2lbs
				
66lbs	28mm 1" 1/8"	16mm 5/8"		

Chrome steel stand.
3 sections, 2 risers.
Ø: 55, 45, 38mm.
Leg Ø: 30mm.
1 leveling leg.

B6039CS (REPLACES B200)

**WIND UP STAND 39
WITH BRAKED WHEELS**

				
71.3in	153.5in	79.1in	55.9in	52.8lbs
				
66lbs	28mm 1" 1/8"	16mm 5/8"		

Chrome steel stand.
3 sections, 2 risers.
Ø: 55, 45, 38mm.
Leg Ø: 30mm.
1 leveling leg.